

10K REFUELER 800 GPM

WWW.GARSITE.COM

GARSITE



FEATURES

Optional

- Recovery Tank 20 Gal
- Additive Injection System
- Thermal Compensation
- Cellular Modem Option
- 4 Liter Visual Sampler and SWD Fitting

Chassis

- EAM RFRD Series w/ TIER III or TIER IV Engine
- Automatic Transmission
- Safety Chassis for Enhanced Maneuverability Around Airport Ramps
- Speed Limited 25 MPH
- Allison Electronic Automatic Transmission
- Aluminum Cab

Tank

- 10,000-Gallon Capacity
- 304 Stainless Steel #4 Finish Construction
- DOT 406 & NFPA 385 Compliance
- Rear Ladder & Roof Safety Line
- Pneumatic Vent and Internal Valve
- Primary and Secondary High-Level Shutoff
- Scully Intellichек 3 System
- Ultrasonic Level Sensor Tied to TCS3000
- (2) Recirculation Stubs
- (2) Drains w/Spring Return Valve

Fueling System – 800 GPM

- Electric Rewind Single-Wrap Hose Reel
- 2.5" x 50' MxM API Fueling Hose
- Underwing Nozzle w/45-PSI HECV
- Scissor Lift Fueling Platform
- 4" Boom or JAC Riser Hose System
- (2) 2.5" x 11' MxM API Fueling Hoses
- (2) Underwing Nozzle w/45-PSI HECV
- TCS Meters w/TCS3000 Electronic Register Heads and Epson Electric Printer
- Facet FWS Vessel w/Water Defense
- Fuel / Defuel
- Recirculation
- Pump (Hydraulic Drive) w/ ByPass Valve

Also Included

- Stainless-Steel Piping
- Stainless-Steel Brackets
- Stainless-Steel Tubing for Sense and Drain Lines
- Multiplex or PLC Control System
- Electric Emergency Shutoff Switches
- (2) 20lb BC Fire Extinguishers w/Brackets
- Camera System w/ LCD Display (Rear-Rounded)
- Reverse Alarm
- NFPA 407 and Logo Decals
- Operation and Maintenance Manual JIG Compliance