

5K REFUELER 300 GPM

WWW.GARSITE.COM

GARSITE



Optional

- Recovery Tank 20 Gal
- Additive Injection System
- Thermal Compensation

FEATURES

Chassis

- International HV607 SBA 4x2
- Automatic Transmission w/PTO
- Modify Exhaust
- Speed Limited at 25 MPH
- Heavy Duty Rear Bumper w/Foldable Ladder Bracket

Tank

- 5,000-Gallon Capacity
- 304 Stainless Steel #4 Finish Construction
- DOT 406 and NFPA 385 Compliance
- Rear Ladder and Roof Safety Line
- Pneumatic Vent and Internal Valve
- Primary and Secondary High-Level Shutoff
- Scully Intellichick System Install w/Dual Socket
- Ultrasonic Level Sensor Tied to TCS3000
- (2) Drains w/Spring Return Valve

Fueling System – 300/100 GPM

- (1) Single Wrap Hose Reel w/Electric Rewind
 - (1) Hose 2,5" x 50'
 - (1) Underwing Nozzle w/45PSI HECV

- 2) Multi Wrap Hose Reel
 - (2) Hose 1,5" x 50'
 - (2) Overwing Nozzles
- (2) TCS Meter and Electronic Register
- Facet Separator Filter Latest Edition
- Fuel / Defuel
- Recirculation
- Pump w/Bypass Valve
- Cla-Val Components

Also Included

- Stainless-Steel Piping
- Stainless-Steel Brackets
- Stainless-Steel Tubing for Sense and Drain Lines
- Multiplex or PLC Control System
- Electric Emergency Shutoff Switches
- (2) 20Lb BC Fire Extinguishers w/Brackets
- Reverse Alarm
- NFPA 407 and Logo Decals
- Operation and Maintenance Manual