



FEATURES

• Chassis

- International HV607 SBA 6x4
- Automatic Transmission W/Hot-Shift PTO
- Exhaust Modified per NFPA 407
- Speed Limited at 25 MPH
- Heavy Duty Rear Bumper W/Foldable Ladder Brackets

• Tank

- 7,000-Gallon Capacity
- 304 Stainless Steel #4 Finish Construction
- DOT 406 & NFPA 385 Compliance
- Rear Ladder & Roof Safety Line
- Pneumatic Vent and Internal Valve
- Primary and Secondary High-Level Shutoff
- Scully Intellicheck 3 System
- Ultrasonic Level Sensor Tied to TCS3000
- (2) Drains W/Spring Return Valve

• Fueling System – 300/100 GPM

- Electric Rewind Single-Wrap Hose Reel
- 2" x 50' MxM API Fueling Hose
- Underwing Nozzle W/45-PSI HECV
- (2) Electric Rewind Multi-Wrap Hose Reels
- (2) 1-1/4" x 50' MxM API Fueling Hoses

- (2) OPW Overwing Nozzles
- (2) TCS Meters W/TCS3000 Electronic Register Heads and Epson Electric Printer
- Facet FWS Vessel W/Water Defense
- Fuel / Defuel
- Recirculation
- Pump W/ByPass Valve

• Available upgrade- 600 GPM

- Scissor Lift Fueling Platform
- 4" Boom or JAC Riser Hose System
- (2) 2.5" x 11" MxM API Fueling Hoses
- (2) Underwing Nozzle W/45-PSI HECV

• Also Included

- Stainless-Steel Piping
- Stainless-Steel Brackets
- Stainless-Steel Tubing for Sense and Drain Lines
- Multiplex or PLC Control System
- Electric Emergency Shutoff Switches
- (2) 20Lb BC Fire Extinguishers W/Brackets
- Reverse Alarm
- NFPA 407 and Logo Decals
- Operation and Maintenance Manual

Optional

- Recovery Tank 20 Gal
- Additive Injection System
- Thermal Compensation
- Cellular Modem Option
- Fire Suppression System in Engine Bay, Main Harness and Controls Box